

GLORIA®

CO₂ extinguishers

- Kitemarked to BS EN3
- Squeeze grip operation
- Corrosion resistant finish
- 2kg model supplied with frost free horn as standard
- CO₂ gas harmless to machinery
- Complete with wall bracket

Type	CO ₂ Aluminium	CO ₂ Aluminium
Capacity (ltr/kg)	2	5
Fire Rating	34B	70B
Height	490	750
Cylinder Diameter (mm)	117	152
Overall Width (mm)	180	310
Filled Weight (kg)	4.91	11.43
Range of Throw (m)	4	4
Duration of Discharge (secs)	8	14
Working Pressure (at 20°C)	56 bar nitrogen	56 bar nitrogen
Temperature Range (°C)	- 30°C to + 60°C	- 30°C to + 60°C
BS EN3 Approved	YES	YES
MED Approved	NO	YES
35kv Conductivity Discharge Test	N/A	N/A
Pressure Relief Valve	YES	YES
Low Freeze Additive	N/A	N/A
Part Number	4705/207	4707/207
Model Number	C20G	C50G

**GLORIA®**

F class

Stored pressure

- Kitemarked to BS EN3
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Lance applicator
- Specifically designed for use on cooking oil fires
- Solution reacts with oil to prevent re-ignition
- Complete with wall bracket

Type	F Class SP	F Class SP
Capacity (ltr/kg)	3	6
Fire Rating	8A 55B 75F	13A 113B 5F
Height	434	675
Cylinder Diameter (mm)	150	170
Overall Width (mm)	141	305
Filled Weight (kg)	7	13
Range of Throw (m)	3	4
Duration of Discharge (secs)	18	30
Working Pressure (at 20°C)	7 bar nitrogen	7 bar nitrogen
Temperature Range (°C)	- 30°C to + 60°C	- 10°C to + 60°C
BS EN3 Approved	YES	YES
MED Approved	NO	NO
35kv Conductivity Discharge Test	YES	YES
Pressure Relief Valve	NO	NO
Low Freeze Additive	NO	NO
Part Number	201F4503/207	201F4502/207
Model Number	W3DFC/FBDP3	W6DRC/FBDP6



3 Lt

6 Lt

