

Type	3L WATER ADDITIVE	6L WATER ADDITIVE	9LWATER	6LWATER SPRAY	1L FOAM	2L FOAM	3L FOAM
Capacity (ltr)	3	6	9	6	1	2	4
Fire Rating	13A	21A	13A	13A	5A 21B	5A 34B	8A 55B
Height	430mm	553mm	620mm	550mm	330mm	390mm	430mm
Cylinder Diameter (mm)	140mm	162mm	184mm	162mm	85mm	110mm	140mm
Overall Width (mm)	210mm	224mm	240mm	225mm	125mm	125mm	210mm
Filled Weight (kg)	5.5	9.5	13.9	9.7	2	3.8	5.5
Range of Throw (m)	>2	>6	>2	>6	>1	>2	>2
Duration of Discharge (secs)	>9S	>9S	>9S	>9S	>6S	>6S	>9S
Working Pressure (at 20°C)	12Bar	12Bar	12Bar	12Bar	12Bar	12Bar	12Bar
Temperature Range (°C)	+5/+60	+5/+60	+5/+60	+5/+60	0/+60	0/+60	0/+60
BS EN3 Approved	Y	Y	Y	Y	N/A	Y	Y
MED Approved	N/A	N/A	N/A	N/A	N/A	N/A	N/A
35KV	Y	Y	Y	Y	N	Y	Y
Pressure Release Valve	Y	Y	Y	Y	Y	Y	Y
Low Freeze Additive	N	N	N	N	N	N	N
Part Number	81/03402	81/03403	81/02905	81/03404	81/03643	81/03405	81/03406
Model Number	WA3	WA6	W9	W6	F1	F2	F3

Type	6L FOAM	9L FOAM	1Kg Powder	2Kg Powder	3Kg Powder	4Kg Powder	6Kg Powder
Capacity (ltr)	6	9	1	2	3	4	6
Fire Rating	13A 144B	21A 183B	5A 34BC	13A 70BC	13A 89B	21A 89BC	27A 144BC
Height	550mm	620mm	330mm	390mm	430mm	495mm	545mm
Cylinder Diameter (mm)	162mm	184mm	85mm	110mm	125mm	140mm	150mm
Overall Width (mm)	225mm	240mm	125mm	125mm	170mm	210mm	225mm
Filled Weight (kg)	9.7	13.9	2.1	3.8	5.5	6.8	9.2
Range of Throw (m)	>4	>4	>2	>2	>2	>4	>4
Duration of Discharge (secs)	>15S	>15S	>6S	>9S	>9S	>9S	>15S
Working Pressure (at 20°C)	12Bar	12Bar	14Bar	14Bar	14Bar	14Bar	14Bar
Temperature Range (°C)	0/+60	0/+60	-30/+60	-30/+60	-30/+60	-30/+60	-30/+60
BS EN3 Approved	Y	Y	Y	Y	Y	Y	Y
MED Approved	N/A	N/A	N/A	N/A	N/A	N/A	N/A
35KV	Y	Y	N/A	N/A	N/A	N/A	N/A
Pressure Release Valve	Y	Y	Y	Y	Y	Y	Y
Low Freeze Additive	N	N	N/A	N/A	N/A	N/A	N/A
Part Number	81/02903	81/02904	81/02908	81/02900	81/03645	81/03407	81/02901
Model Number	F6	F9	PG1A	PG2A	PG3A **	PG4A	PG6A

Type	9Kg Powder	2Kg CO2	5Kg CO2	2L WET	6L WET
Capacity (ltr)	9	2	5	2	6
Fire Rating	34A 183BC	34B	70B	8A 40F	13A 75F
Height	590mm	595mm	770mm	405mm	550mm
Cylinder Diameter (mm)	184mm	103.5mm	136mm	110mm	162mm
Overall Width (mm)	240mm	155mm	180mm	130mm	225mm
Filled Weight (kg)	13.6	6.3	14.2	4.5	11.23
Range of Throw (m)	>4	>4	>4	>2	>2
Duration of Discharge (secs)	>15S	>6S	>9S	>9S	>9S
Working Pressure (at 20°C)	14Bar	65Bar	65Bar	7Bar	7Bar
Temperature Range (°C)	-30/+60	-30/+60	-30/+60	+5/+60	+5/+60
BS EN3 Approved	Y	Y	Y	Y	Y
MED Approved	N/A	N/A	N/A	N/A	N/A
35KV	N/A	N/A	N/A	Y	Y
Pressure Release Valve	Y	Y	Y	Y	Y
Low Freeze Additive	N/A	N/A	N/A	N	N
Part Number	81/02902	81/02906	81/02907	81/03409	81/03408
Model Number	PG9A	K2	K5	W2F	W6F