



GLORIA®



FOAM EXTINGUISHERS - STORED PRESSURE

- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Internal polyethylene lining
- Complete with wall bracket
- Strong protective base*
- Robust discharge hose
- Spray nozzle
- Passed the 35kv conductivity discharge test
- Eco foam model supplied with extra Eco friendly foam
- *Excludes 2ltr models
- 2ltr shrouded head has unique push button
- operation and supplied with wire transport bracket and strap

Type	Foam SP	Foam SP (shrouded head)	Foam SP	Foam SP	Eco Foam	Foam SP
Capacity (ltr)	2	2	3	6	6	9
Fire rating	5A 55B	5A 70B	8A 89B	13A 183B	13A 144B	21A 183B
Height	365	365	485	455	455	610
Cylinder diameter (mm)	108	110	165	170	170	200
Overall width (mm)	145	152	270	260	260	260
Filled weight (kg)	3.5	3.5	5.9	10.5	10.5	14.9
Range of throw (m)	2.5	2	4	4-6	4-6	4-6
Duration of discharge (secs)	22	20	14	36	30	53
Working pressure (at 20°C)	15	15	7	7	7	7
Temperature range (°C)	0 to +60	0 to +60	+5 to +60	0 to +60	0 to +60	0 to +60
BS EN3 approved	✓	✓	✓	✓	✓	✓
MED approved				✓	✓	✓
Part number	4260/207	4256/207	4257/207	4251/207	4261/207	4252/207
Model number	SD2LW	S2LW	S3DLWB	S6DLWB	S6DECO	S9DLWB



Tel: 0161 654 2222 | Freefax: 0800 281 035
 Website: www.thomas-glover.co.uk | Email: tgsales@tgproducts.co.uk



TG Products Ltd, Parkfield House, Manchester Old Road, Middleton, Manchester, M24 4DY