

## POLISHED EXTINGUISHERS - Stored Pressure

- Ideal for environments where hygiene is paramount and when considering architecture
- Highly polished surface finish
- Corrosion resistant construction
- Simple 'seize and squeeze' operation
- Controllable discharge assures efficient use of contents and minimises clean-up
- All extinguishers are re-chargeable
- Carry a 5 year manufacturers warranty if serviced in accordance with BS5306 Part 3

TYPE	WATER SP	WATER SP	AFFF FOAM SP	AFFF FOAM SP	CO <sub>2</sub> POLISHED ALUMINIUM
Capacity (ltr)	6	9	6	9	2
Fire Rating	13A	13A	13A 144B	21A 183B	34B
Height (mm)	550	620	550	620	490
Cylinder Diameter (mm)	162	184	162	184	117
Overall Width (mm)	225	240	225	240	180
Filled Weight (kg)	9.7	13.9	9.7	13.9	4.91
Range of Throw (m)	>6	>2	>4	>4	>4
Duration of Discharge (secs)	>9	>9	>15	>15	>8
Working Pressure (at 20°C)	12 bar	12 bar	12 bar	12 bar	56 bar
Temperature Range (°C)	+5 to +60	+5 to +60	0 to +60	0 to +60	-30 to +60
BS EN3 Approved	NO	NO	NO	NO	NO
MED Approved	NO	NO	NO	NO	NO
35kv Conductivity Discharge Test	YES	YES	YES	YES	N/A
Pressure Release Valve	YES	YES	YES	YES	YES
Low Freeze Additive	NO	NO	NO	NO	N/A
Part Number	9221/00	9222/00	9913/00	9914/00	9705/06
Model Number	FPW6S	FPW9S	FPF6S	FPF9S	FPC2SC
Rating Symbol	A B	A B	A	A	B E

