



Powder extinguishers

Stored pressure

- Kitemarked to BS EN3
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Multi-purpose application
- 1 & 2kg c/w wire transport bracket and securing strap
- 6,9 & 12kg c/w wall mounting bracket
- Strong protective base*
- Robust discharge hose (4,6,9 & 12kg)
- 1kg and 2kg shrouded head models have unique push button operation and supplied with wire transport bracket and strap

*Excludes 1kg and 2kg models

Type	Powder SP	Powder SP	Powder SP	Powder SP	Powder SP	Powder SP SH	Powder SP SH	Powder SP SH
Capacity (ltr/kg)	1	2	4	6	9	12	1	2
Fire Rating	8A 34B C	13A 89B C	21A 89B C	34A 233B C	43A 233B C	55A 233B C	8A 34B C	13A 89B C
Height	280	327	410	500	610	590	180	322
Cylinder Diameter (mm)	90	110	150	150	170	170	90	110
Overall Width (mm)	93	144	300	270	265	265	280	111
Filled Weight (kg)	2.1	3.8	6.7	9.1	13.7	17.3	2.2	3.5
Range of Throw (m)	4	4	6	6	7	7	4	4
Duration of Discharge (secs)	8	9	13	20	17	21	8	13
Working Pressure (at 20°C)	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen	15 bar nitrogen
Temperature Range (°C)	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C
BS EN3 Approved	YES	YES	YES	YES	YES	YES	YES	YES
MED Approved	NO	YES	NO	YES	YES	YES	NO	YES
35kv Conductivity Discharge Test	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Pressure Relief Valve	NO	NO	NO	NO	NO	NO	NO	NO
Low Freeze Additive	NO	NO	NO	NO	NO	NO	NO	NO
Part Number	4358/207	4352/207	4354/207	4356/207	4359/207	4366/207	4351/207	4362/207
Model Number	PD1GA	PD2G	PD4GA	PD6GA	PD9GA	PD12GA	F1GM (GB)	P2GM

