


Code	H6 EN166 1 A KN	
Standard	EN397:2012 + A1:2012 / EN166 CLASS 1	
Name / Description	Hydro-Shield Safety Helmet	
Packaging	4 per carton	
Colours	Black, White	
Sizes	One Size, 53 – 64cm.	

Properties	<ul style="list-style-type: none"> • Shell manufactured from high impact ABS • Hi-Performance, CE - EN397 2012 Certified • Internal retractable visor – EN166 Class 1 Optical • Anti scratch (K) • Anti Fog (N) • Impact (A) - Protection against High-Speed Particles - High energy impact 6mm ball at 190 m/s. • High tensile strength 25mm terylene webbing • Three layer highly absorbent sweatband with embedded foam • Withstands temperatures from -10°C to 55°C • Artificial ageing (durability up to 5 years)
-------------------	--

Areas of Application	The Hydro Shield is suitable for use in a variety of industrial applications. Typical applications are construction and general industry.
-----------------------------	---

Standard	EN 397:2012 + A1:2012 / EN166 CLASS 1 	
-----------------	--	--

Care Instructions	Clean with a damp cloth. If helmet is damaged it will not offer full protection and must be replaced.
--------------------------	---

Symbols	
----------------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk
----------------	--