

# Water fire extinguisher with Cool-Down-Effect

PRO-Line with strike-knob, extinguishing pistol and lance

WKL 6/9 PRO

## The correct extinguisher even for sensitive applications

Portable cartridge operated water fire extinguisher with very good ecological and maintenance-friendly characteristics, approved according to DIN EN 3 for fire class A. Due to the proven special suitability for burning lithium-ion batteries, the extinguisher can be used on batteries up to 642Wh\* (WKL 6 PRO) respectively 1285Wh\* (WKL 9 PRO) or with pouches up to 700Wh (WKL 9 PRO).

### Product features

- Laser-welded cylinder with durable inner coating
- Black anodised metal locking collar
- Perfect handling due to rotatable and extra-long LABS-free quality hose assembly with fabric insert made of synthetic rubber material.
- Rotatable and suppressible extinguishing pistol with pre-mounted extinguishing lance with 5-hole spray nozzle
- Extinguishing agent concentrate fluorine-free, without environmentally harmful PFOS or PFOA
- Conscious renunciation of substances in the water
- Colour coded to local specifications indicating water
- Special suitability for lithium-ion batteries up to 642Wh\* (WKL6PRO) or 1285Wh\* (WKL 9 PRO), at pouches up to 700Wh (WKL 9 PRO)

### Application

- Users of products with lithium-ion batteries up to 642Wh\* or 1285Wh\* or of pouches up to 700 Wh (laptops, e-bikes, e-scooter, cordless, screwdrivers, etc.)
- Hotels, especially bicycle hotels
- Computer/electronic stores (including storage areas)
- Tool departments in retail companies
- File storages/archives/paper and packaging stores
- Offices
- Wood processing
- Textiles
- Municipal facilities
- Administrative and manufacturing areas
- Private households

\* Tests were conducted on cell type 18650

### Note

The suitability test on lithium-ion batteries was conducted by the Dutch institute KIWA!



Type	Part No.	Extinguishing Agent / Qty.	Type	Propellant	Performance LE*	Discharge time / Discharge range	Temperature range	Use on lithium-ion (in Wh) Type 18650	H/W/D in bracket ø – cylinder Weight (kg)
WKL 6 PRO	803841.0000	5,88 l Water + 0,12 l Imprex C	Strike knob and pre-mounted lance	60 g CO <sub>2</sub>	21A	65 sec. / 4m	+5 °C to +60 °C	642Wh	640/400/165 10,8 kg
WKL 9 PRO	803851.0000	8,82 l Water + 0,18 l Imprex C	Strike knob and pre-mounted lance	120 g CO <sub>2</sub>	27A	80 sec. / 4m	+5 °C to +60 °C	1285Wh Pouches: 700Wh	640/430/205 15,6 kg