

PowerX

CO₂ extinguishers

- Kitemarked to BS EN3
- High quality product
- Supplied complete with wall bracket
- Brass valve assembly
- Coated steel levers
- Polyester external coating
- High Tensile Steel body
- Approved to the Pressure Equipment Directive
- Inclusive of pressure release valve
- 5 year warranty

Type	CO ₂ Steel	CO ₂ Steel
Capacity (ltr)	2	5
Fire Rating	34B	70B
Height (mm)	595	770
Cylinder Diameter (mm)	103.5	136
Overall Width (mm)	155	180
Filled Weight (kg)	6.3	14.2
Range of Throw (m)	>4	>4
Duration of Discharge (secs)	>6	>9
Working Pressure (at 20°C)	65 bar	65 bar
Temperature Range (°C)	-30 to +60	-30 to +60
BS EN3 Approved	YES	YES
MED Approved	N/A	N/A
35kv Conductivity Discharge Test	N/A	N/A
Pressure Release Valve	YES	YES
Low Freeze Additive	N/A	N/A
Part Number	81/02906	81/02907
Model Number	K2	K5



PowerX

Wet chemical

Stored pressure

- Kitemarked to BS EN3
- High quality product
- Squeeze grip operation
- Fully refillable
- Controlled discharge
- Specifically designed for use on cooking oil fires
- Solution reacts with oil to prevent re-ignition
- Complete with wall bracket
- 5 year warranty

Type	Wet Chemical Spray SP	Wet Chemical Spray SP
Capacity (ltr)	2	6
Fire Rating	8A 40F	13A 75F
Height (mm)	405	550
Cylinder Diameter (mm)	110	162
Overall Width (mm)	130	225
Filled Weight (kg)	4.5	11.23
Range of Throw (m)	>2	>2
Duration of Discharge (secs)	>9	>9
Working Pressure (at 20°C)	7 bar	7 bar
Temperature Range (°C)	+5 to +60	+5 to +60
BS EN3 Approved	YES	YES
MED Approved	N/A	N/A
35kv Conductivity Discharge Test	YES	YES
Pressure Release Valve	YES	YES
Low Freeze Additive	NO	NO
Part Number	81/03409	81/03408
Model Number	W2F	W6F

