

YOUNGMAN[®]

TRADE APPROVED SINCE 1926

TRADE EXTENSION LADDER Aluminium

- **High performance ladder level gauge for accurate positioning**
- **Slip-resistant square rungs for maximum grip and comfort**
- **Heavy-duty wide stabiliser with slip-resistant feet for added safety**
- **Available in single, double or triple style**



Visit us online to see our full range of products youngmanaccess.com

TRADE EXTENSION LADDER

Aluminium

150kg

MAX. LOAD
(Load includes user, tools,
materials, etc.)




Unique wrap-around top clips have smooth-glide runners which reduce wear and tear

Suitable for Professional & Non-professional use



Approved to the latest EN131 Standard



Slip-resistant square rungs for comfort



High performance ladder level gauge for accurate positioning



Rung clips to secure sections together for safe use and easy transportation



Heavy-duty wide stabiliser with slip-resistant feet for added safety[▲]



SPECIFICATIONS

Product Code	Sections x Rungs	Closed Length (m)	Open Length (m)	Safe Working Height (m)*	Weight (kg)
SINGLE SECTION					
57010220	1 x 10	3.05	3.05	3.65	5.96
57010420	1 x 14	4.18	4.18	4.73	8.57
57010620	1 x 18	5.30	5.30	5.81	11.02
57010720	1 x 20	5.86	5.86	6.35	12.09
DOUBLE SECTION					
57011020 [▲]	2 x 6	1.83	2.95	3.66	6.69
57011120	2 x 8	2.40	4.08	4.75	10.12
57011220	2 x 10	3.01	4.97	5.56	12.34
57011320	2 x 12	3.57	6.09	6.64	14.81
57011420	2 x 14	4.13	7.21	7.72	18.15
57011520	2 x 16	4.70	8.33	8.80	25.72
57011620	2 x 18	5.21	9.12	9.61	28.35
TRIPLE SECTION					
57012020	3 x 6	1.89	4.13	4.76	12.39
57012120	3 x 8	2.45	5.81	6.38	15.42
57012220	3 x 10	3.01	6.93	7.46	22.92
57012320	3 x 12	3.58	8.61	9.09	28.91
57012420	3 x 14	4.14	9.73	10.17	33.05

*Based on 1.75m (5'9") as the average reach height of a person.

[▲]Stabiliser bar is not required or supplied with the 2 section 1.83m model.

**Easy to use
push-up operation**



youngmanaccess.com

Werner UK Sales & Distribution Ltd. Blackwater Trading Estate, The Causeway, Maldon, Essex, CM9 4LJ

YOUNGMAN[®]

©2021 WernerCo Rev. C 04/21